






Smart Lock | Universal Lock Selection Chart

| | Universal Lock (PL106) | Universal Lock II (PL103) |
|---|--|---|
| Panel Thickness  | <p><u>Range:</u> 5.80 mm to 6.35 mm</p> <p><u>Suggested for new construction:</u> 6.00 mm</p> <p><u>Note:</u> Glass should be tempered for safety</p> | <p><u>Range:</u> 4.80 mm to 6.35 mm</p> <p><u>Suggested for new construction:</u> 6.00 mm</p> <p><u>Note:</u> Glass should be tempered for safety</p> |
| Panel Overlap  | <p><u>Range:</u> 22 mm to 110 mm</p> <p><u>Suggested for new construction:</u> 45.00 mm</p> <p><u>Note:</u> Overlap area should be "glass-on-glass" (no trim or boarder)</p> | <p><u>Range:</u> 22 mm to 110 mm</p> <p><u>Suggested for new construction:</u> 45.00 mm</p> <p><u>Note:</u> Overlap area should be "glass-on-glass" (no trim or boarder)</p> |
| Panel Gap  | <p><u>Range:</u> 8.00 mm to 11.50 mm</p> <p><u>Suggested for new construction:</u> 10.00 mm</p> <p><u>Note:</u> Strike plate shims are available as an accessory (see catalog)</p> | <p><u>Range:</u> 4.50mm - 8.00mm</p> <p><u>Suggested for new construction:</u> 5.00 mm</p> <p><u>Note:</u> Strike plate and Lock shims are available as accessories (see catalog)</p> |